

		RTT 15	RTT 18	RTT 22	RTT 26	RTT 30	RTT 32	RTT 34	
	Larghezza utile Useful width Anchura útil Largeur utile	mm	1500	1800	2200	2600	3000	3200	3400
	Dimensioni d'ingombro Overall dimensions Dimensiones ocupadas Dimensions d'encombrement	mm	2860x2030 x1650	3160x2030 x1650	3560x2030 x1650	3960x2030 x1650	4360x2030 x1650	4560x2030 x1650	5160x2030 x1650
	Peso netto (senza cilindro riscaldato) Net weight (without heated cylinder) Peso neto (sin cilindro calentado) Poids net (sans cylindre chauffé)	kg	5600	5800	6200	7400	8600	9200	9600
	Potenza installata Installed power Potencia instalada Puissance installée	kW	49	49	49	49	49	49	49
	Potenza media assorbita Average absorbed power Promedio de la potencia absorbida Puissance moyenne absorbée	kW	22	22	22	22	22	22	22
	Velocità regolabile Adjustable speed Velocidad ajustable Vitesse réglable	m/min	3÷25	3÷25	3÷25	3:25	3:25	3:25	3:25
	Temperatura regolabile Adjustable temperature Temperatura ajustable Température réglable	°C	1÷180	1÷180	1÷180	1÷180	1÷180	1÷180	1÷180
	Pressione Pressure Presión Pression	kg/cm	0÷250	0÷250	0÷250	0÷250	0÷250	0÷250	0÷250

